



Benefits:

- Aluminium base and PC reflector
- Direct replacement for traditional wall-mounted luminaires
- Complete range covering all application requirements in one product
- Up to 55% energy savings compared with luminaires with PL-C lamps

TYPE	Product type: DWG 212 Lunar
FUNCTIONALITY	Initial LED luminaire efficacy: 78 lm/W Color Rendering Index (CRI): > 80 Power supply: Driver included Light source: LED module Color temperature:
ELECTRICAL PARAMETERS	Driver efficiency nominal: Electrical isolation class IEC: Class I Power factor nominal: 0,95 Input voltage: 220 – 240 V
MECHANICAL PARAMETERS	Ingress protection: IP65 Impact resistance: IK08 Installation: Individual
ENVIROMENTAL CONDITIONS	Ambient temperature range: -40 to +40 °C

GENERAL INFORMATION

Warranty period:

3 years

Application:

- Corridors
- Staircases
- Public entrance areas
- Emergency exits
- Parking garages
- Outdoor safety lighting

PRODUCT FAMILY RANGE

Code	Type	Power, W	Initial luminous flux	Color, K	Diffuser	Ingress protection
700151265001	DWG 212 Lunar LED010 12W Opal 830 I	12	1000	3000	Opal	IP 65
700151265002	DWG 212 Lunar LED010 12W Opal 840 I	12	1000	4000	Opal	IP 65
700151265017	DWG 212 Lunar LED 1xE14 OPAL I MAX 22W	n/a	n/a	n/a	Opal	IP 65