

DWL-L

TAKTON



Benefits:

- Up to 50% energy savings compared with TL-D
- Reliable LED technology – maintenance-free
- Direct replacement for conventional waterproof and wall mounted luminaires in terms of light performance
- Universal solution covering various application requirements

TYPE	Product type: DWL-L
FUNCTIONALITY	Initial LED luminaire efficacy: 120-173 lm/W depends on the type Color Rendering Index (CRI): > 80 Power supply: Driver Philips or Tridonic included Light source: LED module with Osram LED chips Color temperature: 4000K as a standard, 3000,5000,6500K on request Managing options: DALI, 1-10V, Motion sensor, wireless connections. Emergency battery operated hours: Philips TrustSight system 3 hours light (Basic or self test) Color tolerance (initial McAdam): 3

ELECTRICAL PARAMETERS

Driver efficiency nominal:

0,92

Electrical isolation class IEC:

Class I or Class II on request

Power factor nominal:

0,93

Input voltage:

220 – 240 V

Power consumption:

33-68 W depending on type

MECHANICAL PARAMETERS

Ingress protection:

IP54

Impact resistance:

02

OVERTIME PERFORMANCE

Median useful life of LED source:

L80B20 - 50 000 hours

GENERAL INFORMATION

Dimensions:

Description	L, mm	H, mm	B, mm	E, mm
DWL-L_120	1260	105	95	740
DWL-L_150	1560	105	95	850

Warranty period:

5 years

Pcs on the pallet:

80

Application:

- Parking garages
- Basements
- Cellars
- Warehouses
- General lighting

PRODUCT FAMILY RANGE

EOC	Description	W	LM	Lm/W	L/B 50000 hours	Weight kg
700151490201	DWL-L_120 4400Lm 36W I 840 IP54 PMMA	36	4400	122	L80/B10	2,7
700151490203	DWL-L_120 7500Lm 49W I 840 IP54 PMMA	49	7500	153	L80/B10	2,7

DWL-L

TAKTON

700151490301	DWL-L_150 5400Lm 33W I 840 IP54 PMMA	33	5400	164	L80/B10	3
700151490303	DWL-L_150 10300Lm 72W I 840 IP54 PMMA	72	10300	160	L80/B10	3