

DCW097-120 110VDC

TAKTON



Benefits:

- Stylish design, made for LED
- Reliable LED technology – maintenance-free
- Direct replacement for conventional waterproof luminaires in terms of light performance, installation flexibility and length

FUNCTIONALITY

Initial LED luminaire lm output:
3600Lm

Optical cover:
Injection molded acrylic (PMMA). As option injection molded polycarbonate (PC)

Color Rendering Index (CRI):
> 80

Power supply:
Takton DC LED driver

Light source:
LED module with Samsung led chips

ELECTRICAL PARAMETERS

Driver efficiency nominal:
0.91

Electrical isolation class IEC:
Class I as a standard, Class II on request

Input Frequency:
50-60 Hz

Power factor nominal:
0,95

Input voltage:
110VDC

Power consumption:
32 W

DCW097-120 110VDC

TAKTON

MECHANICAL PARAMETERS	Ingress protection: IP66 Impact resistance: IK05, IK08 as option Installation: on surface Body material: Flame retardant glass-fibre reinforced polyester
OVERTIME PERFORMANCE	Driver service life time @10% failures: 50 000 h Initial system efficacy: 112 lm/W Luminous flux system tolerance: +/- 5% Median useful life of LED source: L80B20, 50 000 Hours Power consumption tolerance: +/- 5%
ENVIROMENTAL CONDITIONS	Ambient temperature range: -20+35 C
GENERAL INFORMATION	Flammability: Not fire resistant CE mark: CE mark ROHS mark: ROHS mark Application: Electro transport Power substations

PRODUCT FAMILY RANGE

EOC	Name	Initial light output Lm	Power W	Efficacy Lm/W	Length
700151252524	DCW097-120 LED036 32W I 840 IP66 PMMA 110VDC FC	3600	32	112	4ft