

DTP 100

TAKTON



Benefits:

- LED accent-lighting solution with a reasonable payback compared to conventional technologies
- Suitable for food and fashion retailers
- Available in a choice of black or white finish

TYPE	Product type: DTP 100
FUNCTIONALITY	Initial LED luminaire efficacy: 90lm/W Color Rendering Index (CRI): 90 as a standard Power supply: Driver included Light source: COB Philips SLM G7 Premium White
ELECTRICAL PARAMETERS	Electrical isolation class IEC: Class I or II Power factor nominal: 0,95 Input voltage: 220 – 240 V
MECHANICAL PARAMETERS	Ingress protection: IP20 Impact resistance: IK02 Reflector material: Faceted anodized aluminum Body material: Aluminium Color: White or Black Installation: Track mounted

DTP 100

TAKTON

OVERTIME PERFORMANCE	Median useful life of LED source: L80B50, 50 000 Hours Power consumption tolerance: +/- 10%
ENVIROMENTAL CONDITIONS	Ambient temperature range: 0 to +35 °C
GENERAL INFORMATION	Warranty period: 5 years Application: • Shops • Show rooms • Meeting rooms • Circulation areas • Hospitality

PRODUCT FAMILY RANGE

EOC	Description	Colour, K	CRI	Track adaptor	Power, W	FINISH	Beam Angle for the Reflector
700151452101	DTP100 LED008 9W 15DGR WH	3000	90	Global 3phase	9	White	15
700151452102	DTP100 LED008 9W 25DGR WH	3000	90	Global 3phase	9	White	25
700151452103	DTP100 LED008 9W 35DGR WH	3000	90	Global 3phase	9	White	35
700151452104	DTP100 LED008 9W 15DGR BK	3000	90	Global 3phase	9	Black	15
700151452105	DTP100 LED008 9W 25DGR BK	3000	90	Global 3phase	9	Black	25
700151452106	DTP100 LED008 9W 35DGR BK	3000	90	Global 3phase	9	Black	35