DTP 100

TAKTON



Benefits:

- LED accent-lighting solution with a reasonable payback compared to conventional technologies
- Suitable for food and fashion retailers
- Available in a choice of black or white finish

TYPE	**Product type:** DTP 100
FUNCTIONALITY	**Initial LED luminaire efficacy:** 90lm/W **Color Rendering Index (CRI):** 90 as a standard **Power supply:** Driver included **Light source:** COB Philips SLM G7 Premium White
ELECTRICAL PARAMETERS	**Electrical isolation class IEC:** Class I or II **Power factor nominal:** 0,95 **Input voltage:** 220 – 240 V
MECHANICAL PARAMETERS	**Ingress protection:** IP20 **Impact resistance:** IK02 **Reflector material:** Faceted anodized aluminum **Body material:** Aluminium **Color:** White or Black **Installation:** Track mounted

DTP 100

TAKTON

OVERTIME PERFORMANCE	**Median useful life of LED source:** L80B50, 50 000 Hours **Power consumption tolerance:** +/- 10%
ENVIROMENTAL CONDITIONS	**Ambient temperature range:** 0 to +35 °C
GENERAL INFORMATION	**Warranty period:** 5 years **Application:** • Shops • Show rooms • Meeting rooms • Circulation areas • Hospitality

PRODUCT FAMILY RANGE

EOC	Description	Colour, K	CRI	Track adaptor	Power, W	FINISH	Beam Angle for the Reflector
700151452101	DTP100 LED008 9W 15DGR WH	3000	90	Global 3phase	9	White	15
700151452102	DTP100 LED008 9W 25DGR WH	3000	90	Global 3phase	9	White	25
700151452103	DTP100 LED008 9W 35DGR WH	3000	90	Global 3phase	9	White	35
700151452104	DTP100 LED008 9W 15DGR BK	3000	90	Global 3phase	9	Black	15
700151452105	DTP100 LED008 9W 25DGR BK	3000	90	Global 3phase	9	Black	25
700151452106	DTP100 LED008 9W 35DGR BK	3000	90	Global 3phase	9	Black	35