

STYLESPOT L DTP 101

TAKTON



Benefits:

- LED accent-lighting solution with a reasonable payback compared to conventional technologies
- Suitable for food and fashion retailers
- Available in a choice of black or white finish



TYPE	Product type: DTP 101
FUNCTIONALITY	Initial LED luminaire efficacy: 90lm/W Color Rendering Index (CRI): 90 as a standard, 80 on request Power supply: Driver included Light source: Philips SLM G7 Premium White
ELECTRICAL PARAMETERS	Electrical isolation class IEC: Class I or II Power factor nominal: 0,95 Input voltage: 220 – 240 V
MECHANICAL PARAMETERS	Ingress protection: IP20 Impact resistance: IK02 Reflector material: Faceted anodized aluminum Body material: Aluminium Color: White or Black Installation: Track mounted

STYLESPOT L DTP 101

TAKTON

OVERTIME PERFORMANCE	Median useful life of LED source: L80B50, 50 000 Hours Power consumption tolerance: +/- 10%
ENVIROMENTAL CONDITIONS	Ambient temperature range: 0 to +35 °C
GENERAL INFORMATION	Warranty period: 5 years Application: • Shops • Show rooms • Meeting rooms • Circulation areas • Hospitality

PRODUCT FAMILY RANGE

EOC	Description	Colour, K	CRI	Power, W	Lm	Track adaptor	FINISH	Beam Angle for the Reflector
700151452313	DTP101 LED011 14W 930 15DGR WH	3000	90	14	1100	Global 3phase	White	15
700151452314	DTP101 LED011 14W 930 25DGR WH	3000	90	14	1100	Global 3phase	White	25
700151452315	DTP101 LED011 14W 930 35DGR WH	3000	90	14	1100	Global 3phase	White	35
700151452316	DTP101 LED011 14W 930 15DGR BK	3000	90	14	1100	Global 3phase	Black	15
700151452317	DTP101 LED011 14W 930 25DGR BK	3000	90	14	1100	Global 3phase	Black	25
700151452318	DTP101 LED011 14W 930 35DGR BK	3000	90	14	1100	Global 3phase	Black	35