

DTP 102

TAKTON



Benefits:

- LED accent-lighting solution with a reasonable payback compared to conventional technologies
- Suitable for food and fashion retailers
- Available in a choice of black or white finish



TYPE	Product type: DTP 103
FUNCTIONALITY	Initial LED luminaire efficacy: 123lm/W Color Rendering Index (CRI): 80 as a standard. 930, 940 on request Power supply: Driver included Light source: Philips SLM G7
ELECTRICAL PARAMETERS	Electrical isolation class IEC: Class I or II Power factor nominal: 0,95 Input voltage: 220 – 240 V
MECHANICAL PARAMETERS	Ingress protection: IP20 Impact resistance: IK02 Reflector material: Faceted anodized aluminum Body material: Aluminium Color: White or Black Installation: Track mounted

DTP 102

TAKTON

OVERTIME PERFORMANCE	Median useful life of LED source: L80B50, 50 000 Hours Power consumption tolerance: +/- 10%
ENVIROMENTAL CONDITIONS	Ambient temperature range: 0 to +35 °C
GENERAL INFORMATION	Warranty period: 5 years Application: • Shops • Show rooms • Meeting rooms • Circulation areas • Hospitality

PRODUCT FAMILY RANGE

EOC	Description	Colour, K	Track adaptor	COB	Power, W	FINISH	Beam Angle for the Reflector
700151452127	DTP102 LED033 27W 830 15DGR WH	3000	Global 3phase	Philips SLM G7	27	White	15
700151452128	DTP102 LED033 27W 830 25DGR WH	3000	Global 3phase	Philips SLM G7	27	White	25
700151452129	DTP102 LED033 27W 830 35DGR WH	3000	Global 3phase	Philips SLM G7	27	White	35
700151452130	DTP102 LED033 27W 830 15DGR BK	3000	Global 3phase	Philips SLM G7	27	Black	15
700151452131	DTP102 LED033 27W 830 25DGR BK	3000	Global 3phase	Philips SLM G7	27	Black	25
700151452132	DTP102 LED033 27W 830 35DGR BK	3000	Global 3phase	Philips SLM G7	27	Black	35