DTP 104, 105

TAKTON



Benefits:

- LED accent-lighting solution with a reasonable payback compared to conventional technologies
- Suitable for food and fashion retailers
- Available in a choice of black or white finish

TYPE	**Product type:** DTP 104, DTP 104
FUNCTIONALITY	**Initial LED luminaire efficacy:** 95lm/W **Color Rendering Index (CRI):** 90 as a standard, 80 on request **Power supply:** Philips Track Adaptor Driver included **Light source:** Philips SLM G7 Premium white
ELECTRICAL PARAMETERS	**Electrical isolation class IEC:** Class I or II **Power factor nominal:** 0,95 **Input voltage:** 220 – 240 V
MECHANICAL PARAMETERS	**Ingress protection:** IP20 **Impact resistance:** IK02 **Reflector material:** Faceted anodized aluminum **Body material:** Aluminium **Color:** White or Black **Beam angle:** 15, 25, 36, 60 dgr **Installation:** Track mounted

DTP 104, 105

TAKTON

OVERTIME PERFORMANCE

Median useful life of LED source:
L80B50, 50 000 Hours

Power consumption tolerance:
+/- 10%

ENVIROMENTAL CONDITIONS

Ambient temperature range:
0 to +35 °C

GENERAL INFORMATION

Warranty period:
5 years

Application:

- Shops
- Show rooms
- Meeting rooms
- Circulation areas
- Hospitality

PRODUCT FAMILY RANGE

EOC	Description	Colour, K	CRI	Power, W	luminous flux, Lm	Track adaptor	FINISH	Beam Angle for the Reflector
700151452341	DTP104 LED025 27W 930 15DGR WH	3000	90	27	2500	Global 3phase	White	15
700151452342	DTP104 LED025 27W 930 25DGR WH	3000	90	27	2500	Global 3phase	White	25
700151452343	DTP104 LED025 27W 930 36DGR WH	3000	90	27	2500	Global 3phase	White	36
700151452353	DTP104 LED025 27W 930 60DGR WH	3000	90	27	2500	Global 3phase	White	60
700151452344	DTP104 LED025 27W 930 15DGR BK	3000	90	27	2500	Global 3phase	Black	15
700151452345	DTP104 LED025 27W 930 25DGR BK	3000	90	27	2500	Global 3phase	Black	25
700151452346	DTP104 LED025 27W 930 36DGR BK	3000	90	27	2500	Global 3phase	Black	36
700151452354	DTP104 LED025 27W 930 60DGR BK	3000	90	27	2500	Global 3phase	Black	60

700151452347	DTP105 LED038 41W 930 15DGR WH	3000	90	41	3800	Global 3phase	White	15
700151452348	DTP105 LED038 41W 930 25DGR WH	3000	90	41	3800	Global 3phase	White	25
700151452349	DTP105 LED038 41W 930 36DGR WH	3000	90	41	3800	Global 3phase	White	36
700151452355	DTP105 LED038 41W 930 60DGR WH	3000	90	41	3800	Global 3phase	White	60
700151452350	DTP105 LED038 41W 930 15DGR BK	3000	90	41	3800	Global 3phase	Black	15
700151452351	DTP105 LED038 41W 930 25DGR BK	3000	90	41	3800	Global 3phase	Black	25
700151452352	DTP105 LED038 41W 930 36DGR BK	3000	90	41	3800	Global 3phase	Black	36
700151452356	DTP105 LED038 41W 930 60DGR BK	3000	90	41	380	Global 3phase	Black	60